

# 128GB Computer memory DDR4 for Supermicro SuperServer SYS-1029UX-LL1-S16 RDIMM 3DS







#### PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



### Memory Specification



Memory size	128GB
Memory technology	DDR4
ECC support	yes
JEDEC Norm	PC4-23400-R
DRAM Organization	3DS 2H 8Gx4
Rank	4Rx4 (2S2Rx4)
Туре	RDIMM (ECC Registered) 3DS
Number of pins	288 Pin DIMM
Memory data transfer rate	2933MHz @ CL21
Voltage	1,2 Volt
Speciality	3DS
Board dimensions	133,35 x 31,25 (LxB mm)
Operating temperature	0° C - 85° C
Storage temperature	-40° C - +95° C
RoHS compliant	yes
SKU	SP453545
EAN	4067488169229

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



#### System Specifications

The memory is 100% compatible with this sytem:

Supermicro		
Server		
SuperServer		
SYS-1029UX Serie		
SuperServer SYS-1029UX-LL1-S16		
2TB		
16		

<sup>\*</sup> The specifications for the maximum memory upgrade may differ from those of the manufacturer Supermicro. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

#### Information on memory allocation

#### Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.
- When using a multiprocessor system, the memory slots should always be configured identically for each CPU.
- Memory slots without a processor may not be used.
- If memory modules are provided with higher speeds than specified by the system, the memory speed is automatically adjusted to the system specifications.

#### Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
  - Do not touch the gold pins of the memory module  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left($
  - Only touch the sides of the memory module
  - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



## Further memory options for Supermicro SuperServer SYS-1029UX-LL1-S16

8GBSP453541DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory®16GBSP453542DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory®32GBSP453543DDR4RDIMM (ECC Registered)288 Pin DIMMPHS-memory®64GBSP453544DDR4RDIMM (ECC Registered) 3DS288 Pin DIMMPHS-memory®64GBSP453539DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP474987DDR4LRDIMM (ECC LR DIMM)288 Pin DIMMPHS-memory®128GBSP453545DDR4RDIMM (ECC Registered) 3DS288 Pin DIMMPHS-memory®128GBSP453540DDR4LRDIMM (ECC LR DIMM) (ECC LR DIMM) 3DS288 Pin DIMMPHS-memory®	Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
Registered)           32GB         SP453543         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP453544         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           64GB         SP453539         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP474987         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP453545         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP453540         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	8GB	SP453541	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered)           64GB         SP453544         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           64GB         SP453539         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP474987         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP453545         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP453540         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	16GB	SP453542	DDR4		288 Pin DIMM	PHS-memory®	
Registered) 3DS           64GB         SP453539         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP474987         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP453545         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP453540         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	32GB	SP453543	DDR4		288 Pin DIMM	PHS-memory®	
LR DIMM)         LR DIMM)           128GB         SP474987         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP453545         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP453540         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	64GB	SP453544	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM)         LR DIMM)           128GB         SP453545         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP453540         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	64GB	SP453539	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 3DS  128GB SP453540 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	128GB	SP474987	DDR4	,	288 Pin DIMM	PHS-memory®	
·	128GB	SP453545	DDR4	•	288 Pin DIMM	PHS-memory®	
	128GB	SP453540	DDR4		288 Pin DIMM	PHS-memory®	

#### PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.fr/-W5Y



#### Contact Information

PHS-electronic gmbh - www.phs-memory.fr -Karl-Götz-Str. 5 97424 Schweinfurt Allemagne

Phone: +49 9721 784678 E-Mail: info@phs-memory.fr Web: www.phs-memory.fr

All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.fr

#### Product Datasheet | SP453545 128GB Computer memory for SuperServer SYS-1029UX-LL1-S16

