

## 256GB Computer memory DDR4 for Supermicro SuperServer F618R2-RC1PT+ RDIMM 3DS





# Your benefits ✓ verified quality memory ✓ 5 years warranty warranty details see last page ✓ 100% compatible ✓ free support on our hotline ✓ fast delivery

#### PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



#### Memory Specification



Memory size	256GB
Memory technology	DDR4
ECC support	yes
JEDEC Norm	PC4-25600-R
DRAM Organization	3DS 4H 16Gx4
Rank	8Rx4 (2S4Rx4)
Туре	RDIMM (ECC Registered) 3DS
Number of pins	288 Pin DIMM
Memory data transfer rate	3200MHz @ CL22
Voltage	1,2 Volt
Speciality	3DS
Board dimensions	133,35 x 31,25 (LxB mm)
Operating temperature	0° C - 85° C
Storage temperature	-40° C - +95° C
RoHS compliant	yes
SKU	SP467325
EAN	4067488308345

### overRAMing - maximize your RAM



Most systems - including the Supermicro SuperServer F618R2-RC1PT+ - can be upgraded with more memory than originally specified by the device manufacturer.

Therefore, our memory specialists continuously analyze new memory solutions in selected systems. Due to improved manufacturing technologies, new memories with higher performance and capacity will be tested for stability and functionality.

Then the new memory solutions are released for the respective systems. Use the benefits of larger computer memory capacity with the PHSmemory® overRAMing memory solutions.

https://www.phs-memory.fr/-BOR

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



#### System Specifications

The memory is 100% compatible with this sytem:

Device typeServerDevice familySuperServerDevice seriesF618 SerieDevice nameSuperServer F618R2-RC1PT+Maximum memory*4TB / 128GB according to manufacturerNumber of memory sockets16	System manufacturer	Supermicro
Device series  F618 Serie  Device name  SuperServer F618R2-RC1PT+  4TB / 128GB according to manufacturer	Device type	Server
Device name  SuperServer F618R2-RC1PT+  Maximum memory*  4TB / 128GB according to manufacturer	Device family	SuperServer
Maximum memory* 4TB / 128GB according to manufacturer	Device series	F618 Serie
manufacturer	Device name	SuperServer F618R2-RC1PT+
Number of memory sockets 16	Maximum memory*	
	Number of memory sockets	16

<sup>\*</sup> The specifications for the maximum memory upgrade may differ from those of the manufacturer Supermicro. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

Memory modules with our overRAMing-symbol are approved by us for maximum memory expansion.

#### Information on memory allocation

#### Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.
- Memory slots without a processor may not be used.
- If memory modules are provided with higher speeds than specified by the system, the memory speed is automatically adjusted to the system specifications.

#### memory for Intel Xeon CPUs:

CPU / System	RDIMM	LRDIMM	
Xeon E5-16xx v3	8GB RDIMM	32GB LRDIMM	
Xeon E5-26xx v3	16GB RDIMM	64GB LRDIMM DDP	
Xeon E5-46xx v3	32GB RDIMM	128GB LRDIMM DDP	
	64GB RDIMM DDP	128GB LRDIMM 3DS	
	128GB RDIMM 3DS	256GB LRDIMM 3DS	
	256GB RDIMM 3DS		



#### Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
  - Do not touch the gold pins of the memory module
  - Only touch the sides of the memory module
  - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



#### Further memory options for Supermicro SuperServer F618R2-RC1PT+

8GB         SP263619         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           16GB         SP263616         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           32GB         SP263617         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP263690         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           64GB         SP467317         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP467321         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP467312         DDR4         LRDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467325         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467315         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®	Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
Registered)           32GB         SP263617         DDR4         RDIMM (ECC Registered)         288 Pin DIMM         PHS-memory®           64GB         SP263690         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           64GB         SP467317         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP474687         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP467321         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP467312         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467325         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467315         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	8GB	SP263619	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered)           64GB         SP263690         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           64GB         SP467317         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP474687         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP467321         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP467312         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467325         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467315         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	16GB	SP263616	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM)         LR DIMM)           64GB         SP467317         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP474687         DDR4         LRDIMM (ECC LR DIMM)         288 Pin DIMM         PHS-memory®           128GB         SP467321         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP467312         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467325         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467315         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	32GB	SP263617	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 3DS         128GB       SP474687       DDR4       LRDIMM (ECC LR DIMM)       288 Pin DIMM       PHS-memory®         128GB       SP467321       DDR4       RDIMM (ECC Registered) 3DS       288 Pin DIMM       PHS-memory®         128GB       SP467312       DDR4       LRDIMM (ECC LR DIMM) 3DS       288 Pin DIMM       PHS-memory®         256GB       SP467325       DDR4       RDIMM (ECC Registered) 3DS       288 Pin DIMM       PHS-memory®         256GB       SP467315       DDR4       LRDIMM (ECC 288 Pin DIMM       PHS-memory®	64GB	SP263690	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM)         LR DIMM)           128GB         SP467321         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           128GB         SP467312         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467325         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467315         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	64GB	SP467317	DDR4	,	288 Pin DIMM	PHS-memory®	
Registered) 3DS           128GB         SP467312         DDR4         LRDIMM (ECC LR DIMM) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467325         DDR4         RDIMM (ECC Registered) 3DS         288 Pin DIMM         PHS-memory®           256GB         SP467315         DDR4         LRDIMM (ECC 288 Pin DIMM         PHS-memory®	128GB	SP474687	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 3DS  256GB SP467325 DDR4 RDIMM (ECC Registered) 3DS PHS-memory®  256GB SP467315 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	128GB	SP467321	DDR4	,	288 Pin DIMM	PHS-memory®	
Registered) 3DS  256GB SP467315 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	128GB	SP467312	DDR4	•	288 Pin DIMM	PHS-memory®	
· ·	256GB	SP467325	DDR4	•	288 Pin DIMM	PHS-memory®	
	256GB	SP467315	DDR4	•	288 Pin DIMM	PHS-memory®	

#### PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.fr/-W5Y



#### Contact Information

PHS-electronic gmbh - www.phs-memory.fr -Karl-Götz-Str. 5 97424 Schweinfurt Allemagne Phone: +49 9721 784678 E-Mail: info@phs-memory.fr Web: www.phs-memory.fr

#### Product Datasheet | SP467325 256GB Computer memory for SuperServer F618R2-RC1PT+



All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.fr